

PIXID 300: SYSTEM SPECIFICATIONS

System Modules, Test Packages, and Timing Chart

DESCRIPTION

The Pixid 300 is a modular system. It is comprised of several functional modules that are integrated into one complete system used for high-volume manufacturing of camera modules. The modular design of the Pixid systems allows for streamlined assembly and delivery of systems as well as simplified maintenance and operation.

ALIGNMENT MODULE

The alignment module comprises of a 5- or 6-axis (X, Y, Z, θ_x , θ_y , and θ_z) motion stack for lens positioning during the active alignment process. The 365nm UV source option offers high power for the world's fastest cure time with matching adhesives.

ALIGNMENT MODULE SPECIFICATIONS

DEGREES OF FREEDOM	HF5 (X, Y, Z, θ_x , θ_y) or 6 (X, Y, Z, θ_x , θ_y , and θ_z)
LINEAR (X,Y,Z) RESOLUTION	< 0.2 μm
ANGULAR (θ_x , θ_y , θ_z) RESOLUTION	< 0.01 deg
LINEAR TRAVEL RANGE (X,Y,Z,)	50 mm (extended travel available)
ROTATION TRAVEL RANGE (θ_x , θ_y , θ_z)	+/- 5 deg
UV CURE SOURCE	365nm, 385nm LED, or broadband
UV DELIVERY	Integrated into lens grippers



DISPENSE MODULE

The dispense module offers automated, precision dispensing of UV-curable adhesive.

Dispense Technology	Positive Displacement Pump	Micro-jetting Technology
Site Recognition & Dispense Verification	Machine vision camera with illumination	Machine vision camera with illumination
Dispense Pattern Options	Lines, arcs, dots (or any combination)	Lines, arcs, dots (or any combination)
Linear Positional Resolution	< 1 μm	< 1 μm
Dispense Positioning Accuracy (X, Y, Z)	< 25 μm	< 25 μm
Minimum Bead Width	300um	100um



PIXID 300: SYSTEM SPECIFICATIONS

System Modules, Test Packages, and Timing Chart

TARGET MODULES

The Pixid 300 has a large range of target modules from camera module targets of different wavelengths and field of views to collimators for far object distance to speckle-free targets and beam profilers for projected images. Targets can be customized to your application.

NARROW FOV TARGET MODULE SPECIFICATIONS

AVAILABLE TARGET OBJECT DISTANCE WITHOUT RELAY OPTICS	10mm - 1200mm
SIMULATED TARGET OBJECT DISTANCE WITH RELAY OPTICS	600mm-infinity
MAXIMUM LENS FOV WITH RELAY OPTICS	70 degrees
OPTICAL FIELD HEIGHT FOR ALIGNMENT AND TEST	Configurable
NUMBER OF OFF-AXIS FEATURES FOR ALIGNMENT/TEST	4 to 16 (or more dependent upon sensor resolution)
NUMBER OF ON-AXIS FEATURES FOR ALIGNMENT/TEST	1
FEEDBACK FOR ALIGNMENT	MTF (ISO12233)
BACKLIGHT UNIFORMITY MAX VARIATION	10%
STANDARD BACKLIGHT COLOR	White
OPTIONAL BACKLIGHT COLORS	Red (625nm), Blue (470nm), Green (530nm), NIR (850nm or 940nm), FWIR

WIDE FOV TARGET MODULE SPECIFICATIONS

MAXIMUM TARGET OBJECT DISTANCE	1.2m
MAXIMUM LENS FOV	190 degrees
OPTICAL FIELD HEIGHT FOR ALIGNMENT AND TEST	Configurable
NUMBER OF OFF-AXIS FEATURES FOR ALIGNMENT/TEST	4 to 16
NUMBER OF ON-AXIS FEATURES FOR ALIGNMENT/TEST	1
FEEDBACK FOR ALIGNMENT	MTF (ISO12233)
BACKLIGHT UNIFORMITY MAX VARIATION	10%
STANDARD BACKLIGHT COLOR	White
OPTIONAL BACKLIGHT COLORS	Red (625nm), Blue (470nm), Green (530nm), NIR (850nm or 940nm), FWIR



PIXID 300: SYSTEM SPECIFICATIONS

System Modules, Test Packages, and Timing Chart

COLLIMATOR TARGET MODULE SPECIFICATIONS

Kasalis offers both fixed focus and motorized variable focus collimators.

AVAILABLE TARGET OBJECT DISTANCE	Up to infinity
MAXIMUM LENS FOV	190+ degrees
OPTICAL FIELD HEIGHT FOR ALIGNMENT AND TEST	Configurable
NUMBER OF OFF-AXIS FEATURES FOR ALIGNMENT/TEST	4 to 20+
NUMBER OF ON-AXIS FEATURES FOR ALIGNMENT/TEST	1
FEEDBACK FOR ALIGNMENT	MTF
BACKLIGHT UNIFORMITY MAX VARIATION	10%
STANDARD BLACKLIGHT COLOR	White
OPTIONAL BLACKLIGHT COLORS	Red (625nm), Blue (470nm), Green 530nm), NIR (850nm or 940nm), FWIR, other wavelengths possible upon request

PROJECTOR TARGET MODULE SPECIFICATIONS

Kasalis offers any combination of the following options for projector alignment targets.

AVAILABLE TARGET OBJECT DISTANCE	Up to 1m
OPTION	Beam profiler
OPTION	Speckle-free projection screen with imaging camera
OPTION	Optical power meter

INDEXING MODULE

The indexing module includes four positions. It also rotates, allowing for parallel processing in the Pixid system.

TIME TO INDEX AND ENGAGE CAMERA FIXTURE	Less than 1.5 seconds
# OF POSITIONS	4
POSITION 1 FUNCTION	Load/Unload
POSITION 2 FUNCTION	Automated adhesive dispense, sensor tests, adhesive validation
POSITION 3 FUNCTION	Active alignment, adhesive cure, optical test
POSITION 4 FUNCTION	Spare position for additional tests

BASE MODULE AND SAFETY ENCLOSURE

The safety enclosure protects the operator from moving parts and UV light exposure and also prevents external light from affecting the alignment and testing.



PIXID 300: SYSTEM SPECIFICATIONS

System Modules, Test Packages, and Timing Chart

BASE MODULE SPECIFICATIONS

SYSTEM FOOTPRINT	1100mm x 850mm (not including load/unload area)
FACILITY POWER REQUIREMENT	110VAC/15A or 220VAC/7.5A
FACILITY AIR REQUIREMENT	80 psi minimum
FACILITY VACUUM REQUIREMENT	House vacuum (if needed)
MACHINE INTERNAL CLEANROOM CLASS	Class 100 (ISO 5)
LIGHT TOWER	Included
PRIMARY OPERATOR INTERFACE	Touch panel monitor
CE CERTIFICATION	<ul style="list-style-type: none"> • EN 60204-1 • BS EN ISO 12100:2010 • EN ISO 13849

CONTROL SYSTEM

The control system software is designed to allow for process setup, modifications, process sequencing and tracking, status reporting, operator prompts, maintenance operations, system calibration, display of align and test results, and data logging to standard database formats. The operator language is configurable for your geographic region.

FIXTURES

Kasalis provides a fixture design service for mechanically and electrically engaging your device (camera module or projection module) to the Pixid system.

CAMERA INTERFACE	Parallel, MIPI, HiSpi, Serial LVDS, sub-LVDS, SLVS-EC
CAMERA COMMUNICATION	SPI, I2C
CAMERA MODULE PACKAGE TYPE	COB, CSP, TSV, PCB mounted, connector, BGA
SENSOR RESOLUTION	Any

TEST PACKAGES

The Pixid 300 Pro includes a standard test package. Customers can also choose from several optional test packages, as noted in the table below.

PIXID 300 PRO: TESTING PACKAGES AVAILABLE

Test Package Name	Tests in Package	Standard or Optional
Standard Tests	<ul style="list-style-type: none"> • MTF • Focus Symmetry • Field Curvature • Image Contrast • Centration 	Included
Advanced Lens Tests	<ul style="list-style-type: none"> • Chromatic Aberration • Astigmatism • Field of View 	Optional
Advanced Sensor Tests	<ul style="list-style-type: none"> • Hot/Dead Pixels • Dark Signal • Temporal Noise 	Optional
Advanced Camera Tests	<ul style="list-style-type: none"> • Color Reproduction • Dynamic Range 	Optional
Particle Detection	<ul style="list-style-type: none"> • Advanced Particle Detection 	Optional



PIXID 300: SYSTEM SPECIFICATIONS

System Modules, Test Packages, and Timing Chart

TOP LEVEL PROCESS FLOW: TIMING CHART FOR CAMERA MODULE

The below process flow chart illustrates how camera modules will move through the Pixid 300 system, in parallel, in order to obtain the optimal TAKT time.

Seconds	Load-Unload Station	Dispense Module	Align Module
0	Disengage camera fixtures and rotate index table 90 degrees.		
1			
2	Unload completed camera module. Load next sensor and lens.	Power on image sensor and begin streaming images.	Power on image sensor, pick up lens, and move lens to align start
3		Optional particle test and inspect sensor for dispense datum.	Active alignment: Tip/tilt correction, focus, optical centration, and MTF verification.
4		Dispense UV curable adhesive with primary dispense head	
5			
6			
7		Post-dispense vision verification of dispensed bead or dot.	
8			
9		UV Cure	
10			
11			
12			
13	Ungrip lens housing and final MTF verification		
14			
15			

Production Throughput **Up to 240 modules per hour**

About Kasalis

Kasalis is a proven market leader in active alignment and designs industry leading optical alignment manufacturing systems. Kasalis systems precisely align and assemble optical electronic devices for a variety of products and industries that include AR and VR headsets, LiDAR systems, laptops, cell phones, cameras and automotive displays. With over 20 years of experience, Kasalis has emerged as a premier active alignment technology company driving the enhanced development of current and next-generation capabilities of electronic devices.

Kasalis is a technology division of Jabil, a \$26 billion global company with over 50 years of experience delivering technology, manufacturing and supply chain solutions to the world's leading brands.